ViewSonic MiewBoard IFP8652-2F

Key Features

- Seamless plug-and-play connectivity with triple USB-C ports
- Intuitive Android[™] 13 customizable launcher with draggable apps and widgets
- Advanced security controls and compliance standards that safeguard your data
- Enhanced collaboration with integrated myViewBoard software powered by Octacore CPU



*Google, Android, YouTube, Google Maps and other marks are trademarks of Google LLC.

Product **Description**

Tap into limitless learning with the ViewBoard IFP52-2F Series. Certified under the Android[™] Enterprise Device License Agreement (EDLA), it seamlessly harmonizes the Android[™] 13 operating system with myViewBoard software and Google Play Store access to deliver enriched learning experiences enhanced by robust security features. Collaborate with split-screen multitasking; enjoy seamless connectivity and streamlined workflows empowered by triple USB-C ports and vCast wireless screen casting; and captivate remote and in-person students alike using its built-in microphones and front-facing speaker. Complete with a full range of compatible accessories, it invigorates learning experiences to take student engagement to new heights.

Visit Us

www.viewsonic.com



viewsonic.com/eu/products/sheet/IFP8652-2F

	viewsonic	c.com/eu/products/sheet/IFP	8652-2F
DISPLAY		POWER	
Panel Size:	86"	Voltage:	100-240VAC +/- 10% Wide Range
Panel Type:	TFT LCD Module with DLED	Consumption:	148.12W (Energy Star) / Off: <0.5W
ranei type.	Backlight, VA	ERGONOMICS	
Display Area (mm):	1895.04 (H) x 1065.96 (V) (85.6"diagonal)	Wall Mount (VESA®):	800 x 600
Aspect Ratio:	16:9	OPERATING CONDITIONS	
Resolution:	UHD 3840x2160(Pixels)	Temperature (° C):	0°C to 40°C
Colors:	1.07B colors	Humidity:	20% ~ 80% RH non-condensing
Brightness:	400 nits (typ.), 450 nits (max.)	DIMENSIONS (W X H X D)	
Contrast Ratio:	4000:1(Typ.) 5000:1(Min. with DCR enabled)	Physical (inch / mm):	1971.16 x 1212.54 x 121.38 mm / 77.605 x 47.738 x 4.779 in
Response Time:	≤7ms	Packaging (inch / mm):	2116 x 1330 x 225 mm / 83.3 x 52.4 x
Viewing Angles:	H = 178, V = 178 typ.		8.9 in
Backlight Life:	50,000 hrs (typ).	WEIGHT	162 11b/74kg
Surface Treatment:	Hardness: 7H. Anti-glare coating	Net (lb / kg):	163.1lb/74kg
		Gross (lb / kg):	185.2lb/84kg
Orientation:	Landscape	REGULATIONS	
PLATFORM		NRTL w/ CA,FCC-B w, DOE Ener CB, RoHS Green BOM	gy Star,DOE EPEAT, CE EMC, LVD or
Processor:	Octa-Core CPU (A73*4 + A53*4)	& RoHS DoC, ErP, REACH SVHC List & DoC, EEL, WEEE	
RAM:	8GB	PACKAGE CONTENTS	
Storage:	64GB	1. 3m power cord by ship area	
тоисн		2. Remote control with AAA battery	
Type/ Tech:	UFT (Ultra Fine Touch) Technology	(new VS remote control)	
Touch Resolution:	32767 x 32767	3. 3m touch USB cable	
Touch Point:	Windows: 40 points touch, Android: 20 points touch	4. Touch pen x 2 (a set)	
		5. Quick Start Guide	
INPUT	x3 (Frontx1:HDMI2.0 with CEC ;	6. RS232 adapter	
HDMI:	Rearx2:HDMI2.1 with CEC/ARC & HDMI 2.0 with CEC)	7. Clamp x 5	
RGB / VGA:			
	x1	8. Camera Plate	
DisplayPort:	x1	9. Screw x 8 (camera 2+2, wall mount 4)	
Audio:	x1 (PC audio in)	10. HDMI cable 3m	
RS232:	x1	11. AAA Battery x 2	
OPS:	module slot x 1	12. Compliance statement	
OUTPUT		COMPATIBLE SLOT-IN PC	
HDMI:	x1	VPC25-O-1B series/VPC27-O-1B	series/VPC35-W53-G1/VPC37-W53-G1
Audio:	x1 (Earphone out)		
SPDIF:	x1		
LAN			
RJ45:	x2		
USB			
Туре А:	USB3.0 x 4 (Front x 2; Rear x 2) USB 2.0x1 (Rear)		
Type B:	USB 3.0 x3(Front x1; Rear x 2)		
Туре С:	x3 (Front x1 with USB3.0, DP1.2, Ethernet 100M, PD 65W; Rear x1 with USB3.0, DP1.2, Ethernet 100M, PD 100W; Rear x1 with USB3.0 data only)		
SPEAKERS			
20W x 2 front soundbar + 20W x 1	subwoofer		
MICROPHONE			
built-in 8-array microphone			
TOP CAMERA PLATE			
Yes			
EMBEDDED OS			
Android 13			
BUNDLE SOFTWARE			
Basic Annotation Software:	myViewBoard WhiteBoard for Android		
Pro Annotation Software:	myViewBoard WhiteBoard for Windows (embedded in VPC)		
Wireless Presentation:	myViewBoard Display, vCast		
SPECIAL FEATURES	, Honzoura Diopidy, Yodot		
All-in-one USB port:	USB 3.0 "SmartPort USB" to all channels.		
Simple LAN sharing between IFP and slot-in device:	10/100/1000M (USB Type-C 10/100, Android & PC 10/100/1000)		
Light Soncor:	V		

Copyright © ViewSonic Corporation 2000-2023. All rights reserved.

Light Sensor:

Yes